

## Slim Duct

Slim Design




ALL  
DC




### Slim design

The slim design allows installations where ceilings are narrow.  
Drain hose as standard accessory



### Drain pump is standard accessory

Simple flat Auto Louver will provide comfort airflow and harmonize with luxury interior.




### Selectable with a wide range of static pressure

By using the DC fan motor, it is possible to change the static pressure range from 0 to 90 Pa.  
The change of static pressure range is possible by remote controller.



Static pressure range  
0 to 90 Pa

### Wide operation range



### Auto louver grille kit (Option)

The optional clean-looking flat Auto louver blends into any interior and provides a comfortable airflow.



Model: ARXG18KLLAP



### Specifications

Model name	Indoor unit		ARXG18KLLAP
	Outdoor unit		
Power Source	V/Ø/Hz		230/1/50
Cooling (Min.-Max.)	kW		5.2 (0.9-5.4)
Btu/h			17,700 (3,100-18,400)
Capacity	Heating (Min.-Max.)	kW	6.0 (0.9-6.3)
		Btu/h	20,500 (3,100-21,400)
Input Power	Cooling/Heating	kW	1.66/1.71
EER	Cooling	W/W	3.13
COP	Heating		3.51
Running Current	Cooling/Heating	A	7.6 / 7.9
Moisture Removal		l/h	2.0
	Indoor (Cooling)(H/M/L/Q)		32 / 30 / 29 / 27
Sound Pressure Level	Indoor (Heating)(H/M/L/Q)	dB(A)	32 / 30 / 29 / 27
	Outdoor		51/52
Airflow Rate (Cooling/Heating)	Indoor (High)	m³/h	940/940
	Outdoor		1,710/1,840
Net Dimensions H x W x D	Indoor	mm	198 x 900 x 620
Weight	Indoor	kg	20
	Outdoor	mm	542 x 799 x 290
Piping Connections (Small / Large)	Indoor	kg	33
Drain port Diameter (I.D./O.D.)	Indoor	mm	6.35/12.70
Max. Pipe Length (Pre-Charge)	Indoor	m	25/32
Max. Height Difference	Indoor	m	20 (15)
Operating Range	Cooling	°CDB	-10 to 46
	Heating		-15 to 24
Refrigerant			R32

### Optional parts

Compact wired remote controller:	UTY-RCRGZ1	Simple remote controller:	UTY-RSRG
Wired remote controller (touch panel):	UTY-RNRGZ5	UTY-RSNGM	UTY-TFSZ2
Wired remote controller:	UTY-RLRG	WLAN adapter:	UTY-LBTGM
	UTY-RNNGM	IR receiver unit:	UTY-VMSX
	UTY-RVNGM	MODBUS converter:	UTY-VKSX
Simple remote controller (without operation mode):	UTY-RHRC	KNX Converter:	UTD-GXTB-W

Network Converter for single split (DC power supply type): UTY-VTGX  
Network Converter for single split (AC power supply type): UTY-VTGV  
External connect kit:  
Remote sensor unit:  
External switch controller:  
UTY-XWZXZG  
UTY-XSZXZ1  
UTY-TERX

### Dimensions

(Unit: mm)

